

AROCS 2651 L 6X4



Palfinger AG

Mercedes-Benz
Trucks you can trust



Orderdata (Order 1-29377037)

Code	Description	Code	Description
A1D	Front axle 8.0 t	K5M	Tanks, lockable
A1Y	Front axle, straight version	K5S	Protective cap for AdBlue metering system
A2G	Rear axle, crown wheel 300, planetary, 13.4 t	K7D	Exhaust system, tailpipe to right and outwards
A5P	Axle ratio i = 3.714	L0A	Illumination regulation, in acc. with UN-R 48.06
B1B	Electronic braking system with ABS and ASR	L1C	LED daytime running lamps
B1F	Heating, electronic air-processing unit	L1D	Automatic main/dipped beam and cornering light
B1H	Electr. compressed air supply and control, centre	L1M	LED fog lamps
B1Z	ABS, disengageable	L1P	LED tail lights
B2A	Disc brakes on front and rear axle	L1W	LED turn signals in light signature
B2D	Cover plate for brake discs	L2H	Side marker lamps, flashing
B2X	Parking brake, electronic	L9A	Pre-installation for rotating beacons
B4A	Condensation monitoring, for compressed air	L9B sys.	Pre-installation for additional headlamps
B4M	Air reservoir, steel	L9C	Pre-installation for additional headlamps, roof
B4Z	Air reservoir, additional	L9G	Pre-installation for flood lamp, cab rear wall
B5B	Trailer brake, 2-line	M0C	Bottom shell to prevent swirling-up of dust
C0M	Frame overhang 1350 mm	M0Q	Noise regulation acc. to UN-R 51.03, phase 2
C1Z	Wheelbase 3900 mm	M3D	Eng. OM471, inline 6, 12.8 l, 375kW (510hp), 2500 Nm
C5O	Preparation for special front-mounted equipment	M4X	Engine version Euro VI, E
C5P	Bolted frame	M5D	3. Engine generation OM471
C6C	Steering, single-circuit	M5V	High Performance Engine Brake
C6I	Power steering pump, controlled	M6L	Air compressor, 2-cylinder
C6Q	Stabiliser, front axle	M7I	Insect screen in front of cooling system
C6U	Extra anti-roll bar, rear/trailing axle	M7T	Water pump, governed
C7J	Battery carrier, batteries side by side	M8B	Air intake behind cab, mounted
C8F	Wing, for chassis transit	N6Z	Transmission oil cooling
C9S	Deletion mounting parts, on frame	N7M	Engine PTO, rear, c, hydraulic pump ISO 7653D
C9Y	Deletion, rear underride guard (ECE)	OWY	Interior measures upgrade
C9Z	Deletion, front underride guard (ECE)	O0A	Coolant service interval, long for non-SWR
D0A	Leather steering wheel	O0T	TruckLive
D0L	Smokers pack	O1N	Detachable parts for offline cab
D0S	Compressed-air connection, in cab	O1T	Interior colour greige/anthracite
D1C	Driver's suspension seat, comfort	O1Z	Steering, indirect
D1N	Fold-up co-driver's seat	O2F	PTO, NMV or engine, rear
D2N	Driver's seat backrest, release mechanism	O2N	Starter Melco 95P65
D2Y	Seat belt monitor	O2X	Optimised cab separation point, supply
D4Y	Sunblind, side, driver's side	O3B	Comfort Package, for S/M cab
D5S	Seat cover, prem. flat-weave fabric, driver's seat	O3K	Active Safety
D5T	Seat cover, prem. flat-weave fabr., passenger seat	P0Q seat	Cover, for wheel arch and engine
D5Y	Rubber mats, driver's and co-driver's side	P0S	Space f. control unit betw. driv. seat & door pocket

Orderdata (Order 1-29377037)

D6G	Automatic climate control	Q1N	Front spring, 8.0 t, 3-leaf
D6I	Residual engine heat utilisation	Q3Y	Lowered frame, w/o residual bellows pressure ctrl.
D6Z	Construction-site filter	Q7K	Trailer coupling, standard, D40, Rockinger
D7G	Stowage compartment lid, driver and co-driver	Q8G	Hand lever, bottom, for trailer coupling side
D7P	Tray, low, on engine tunnel	Q8R	End cross-member, reinforced
D7Z	Stowage net, on rear wall	R0L	Tyres, customer request, FA
D8A	Roof hatch/vent, roof	R0N	Tyres, customer request, RA
E0D	Battery sensor, Hella	R0O	Tyres, customer request, 2nd RA/twinty.trail.axle
E0F	Batteries from company Exide	R0Z	Wheel-nut cap
E0V	Highload parameter, level 1	R1Q	15-degree tapered rims, 9.00 x 22.5
E1C	Batteries 2 x 12 V/220 Ah, low-maintenance	R1T	15-degree tapered rims, 11.75 x 22.5, front axle
E1N	Alternator 28 V/100 A	S1D	Stability Control Assist (ESP)
E3E	Additional socket, 12 V/15 A, co-driver footwell	S1F	Roll Control Assist
E3L	Socket, 24 V/15 A, co-driver footwell	S1H	Lane Keeping Assist
E3W	PSM, 2nd generation	S1L	Attention Assist
E4C	Additional functions, for body manufacturer	S1O	Traffic Sign Assist
E5A	No. 1 switch, for non-MB body electrics	S1Y	Tyre pressure monitor
E5B	No. 2 switch, for non-MB body electrics	S2D	Active Brake Assist 6
E5H	Switch for night-time driving light	S2H	Active Sideguard Assist 2
E6A	Trailer socket, 24 V, 15-pin	S2L	Frontguard Assist
E6Y	Reverse warning, comb. with hazard warning lights	S2Q	Sensor position, side radar, widened
E7F	Cable remote control for air suspension	S4A	Pre-installation for alcohol test on start-up lock
E9G	Provision for fitting electrical devices	S5A	Speed limiter, 90 km/h (56 mph), ECE
F0G	Side module, N3G vehicle	S5Z	Cruise control
F0Y	Mirror cover, construction vehicle	S8A	First aid kit
F1B	M-cab ClassicSpace, 2.30 m, tunnel 170 mm	S8C	Hazard warning triangle
F1Q	M-cab	S8D	Warning lamp
F2B	Floor variant, tunnel 170 mm	S8E	Reflective safety jacket
F2G	Cab width 2.30 m	U1W	AdBlue lines, water-heated
F2N	Cab, 600 mm attachment height	U2G	Exhaust box
F2U	ClassicSpace	U2M	Control code, ASAM
F3B	Cab mountings, comfort, steel-sprung	U2T	Control code, exhaust box, rear outlet
F3W	Cab tilting mechanism, mechanical-hydraulic	U2V	Control code, catalytic converter kit 2
F4I	Cab rear wall, with window	U3D	Control code, CAN star points, classic
F4X	Stowage compartment exterior flap, left	U3F	Control code, global AdBlue sensor (GMS DEF)
F5L	Sun visor, exterior, transparent	U3N	Control code, navigation map, EU region
F5Y	A-pillar trim	U3S	3rd-generation electronics architecture
F6D	Windscreen, tinted, with filter band	V0Q	Vehicle version in acc. w. GSR, phase B
F6I	Front mirror, heated	V0T	Vehicle class N3G, off-road vehicle

Orderdata (Order 1-29377037)

F6L	Main mirror, manoeuvring setting, co-driver's side	V0U	Overhang angle, front, minimum 25 degrees
F6R	Air horns, cab roof	V0W	Breakover angle, minimum 25 degrees
F7B	Bumper, with steel corners	V0X	Ground clearance under front axle, minimum 250 mm
F7D	Bumper centre section w. towing eyes, coupling	V0Y jaw	Ground clearance under rear axle, minimum 250 mm
F7T	Door extension	V1B	Arocs
F7Y	Cab entrance, left/right, movable	V1W	Standard
F7Z	Step, with grab rail on roof	V2J	Arocs model generation 5
F8B	2 remote control keys	V6D	Min. spec., skip loader
F8E	Locking system, with central locking	V7J	Body type: roll-off
F8F	Extended central locking	V8A	Chassis number FIN
F8V	Light sensor	V9G	Technical changes model year October
F8W	Rain sensor	W2V	Weight variant 26.0 t (8.0/10.5/10.5)
G0B	Powertrain, 44 t to 80 t	X2A	Model identification, acc. to weight variant
G0K	Drive program, economy/power	X2E	Model plate, EU
G0R	Transmission support arms, optimised for removal	X2T	Maintenance Documentation
G0T	Predictive Powertrain Control	X2Y	Registration certificate, Part II, prepared
G2F	Transmission G 330-12/11.63-0.77	X3O	Mercedes-Benz OnRoadService
G5B	Double-disc clutch	X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
G5G	Mercedes PowerShift 3	X4H	Instrument/labels/documentation, German
G5L	PowerShift Advanced	X4S	ATS warranty according to GTC, 4th year/340,000 km
G5Y	Tachograph calibration, digital, ex factory	Y1B	Control of colours, high-runner colours
I2H	Tyres, tubeless, size 315/80 R 22.5, rear axle	Y1H	Assignment of cab paintwork, NFL North
I2P	Tyres tubeless, 385/65 R 22.5, fr./lead./trl. axle	Y4J	2 wheel chocks
I4I	Wheel arrangement 6x4	Y4Y	Tyre inflating hose
I5F	26.0-tonner	Y4Z	Compressed-air gun, with hose
I6A	Rigid chassis	Y9X	Deletion, bracket, wheel chock
I6I	Vehicle production plant Wörth	Z1H	EBS, Wabco
I6K	Heavy-duty model series, new generation from 18 t	Z1S	Level control equipment, item 1
I6M	Heavy-duty vehicles from 18 t, off-road	Z1X	EAPU equipment, item 1
I6X	Air suspension, rear axle	Z3A	Switch module 1, type A
J0U	Remote update of driving assistance map	Z3D	Switch module 2, type B
J1M	Dig. tachograph, 2nd gen., version 2, ADR	Z3F	Switch module 7
J1S	Tachograph manufacturer VDO	Z3H	Side marker lights, 1st pair
J2G	Digital radio	Z3J	Side marker lights, 3rd pair
J2K	Speaker, 2-way system	Z3K	Side marker lights, 4th pair
J2U	Navigation system	Z4B	Domestic (Germany)
J3U	Requirement: FleetBoard Manager app	Z4O	Tank cross-section, narrow
J3Z	Axle load measuring device	Z4Q	Tank cross-section, low
J6C	Multimedia Cockpit, interactive	Z5E	OM 471
J6W	Reversing camera, towing vehicle end	Z5G	Fan position, on crankshaft

Orderdata (Order 1-29377037)

J7A	Truck Data Center 8	Z5K	Fan ratio, 1:1.2
J7V	Driving assistance map, Europe region	Z5P	Clutch supplier F&S
J8S	Preinst. & display for up to 2 additional cameras	Z5V	Starter with M10, HDEP
J8U	Pre-installation for Truck Data Center 8	Z5X	Left-hand drive
J9A	Pre-installation for CB radio, 12 V, DIN slot	Z5Y	Vehicle, for right-side traffic
J9D	Provision for fitting toll tracking	Z7J	Aluminium battery lines
K0T	Main tank, left	Z7K	Paint, additional control code
K1C	Tank, 290 l, left, 650 x 565 x 950 mm, aluminium	Z7L	Exterior mirrors, painted
K3V	AdBlue tank, 60 l, left		

SP-REQ. no.	Description
-------------	-------------

HP 20 A TEC hooklift



M 18-22

Assembly of hooklifts 18-22t lifting capacity

Equipment assembly ABROLLKIPPER according to Palfinger and truck manufacturer assembly guidelines on a ready-to-install chassis with suitable power take-off to be delivered carriage paid ex works.

Truck parameterization.

Contour marking in accordance with directives 76/756 EEC and UN ECE R48.

Assembly of the hydraulic and electrical system incl. oil filling and PDI (pre-delivery inspection - according to checklist).

For hooklifts with 18-22t lifting capacity

T

Shorten frame / move cross member

Shortening the frame overhang incl. engaging the coupling traverse and relocating the air and light lines

MS

Fitting truck marker lights

Fitting the side marker lights supplied with the truck

UFS-Mo

Mounting underride guard (all types)

Assembly flat rate UFS (all types)

SSV-Mo

Fitting side protection device (SSV)

Assembly flat rate for provided SSV (side protection device)

KFL-Mo

Mounting mudguards

Assembly of the mudguards provided

AS 2

Supply & fit 2 LED worklights

Delivery and installation of 2 LED worklights;

DUO

Supply & fit DUOMATIC air coupling

Supply and install "DUOMATIC" air connections

MLL

Assembly and painting of Palfinger rear light holder

Assembly of the provided GPA rear light holder M9001417 incl. painting

SB

Supply & install shovel and broom holder

Delivery and installation of a shovel and broom holder (without tools)

TÜV

TÜV approval

Have inspection carried out

TACHO

TACHO inspection

Tachograph