

AROCS 1835 K 4X2



Putzmeister Concrete Pumps GmbH / INTERMIX

Mercedes-Benz
Trucks you can trust



Orderdata (Order 1450613060)

Code	Description	Code	Description
A1D	Front axle 8.0 t	K5M	Tanks, lockable
A1Y	Front axle, straight version	K5Q	Fuel screen, tank filler neck
A2G	Rear axle, crown wheel 300, planetary, 13.4 t	K5S	Protective cap for AdBlue metering system
A5Y	Axle ratio i = 4.333	K7I	Exhaust system, on frame, right, tailpipe inwards
B1B	Electronic braking system with ABS and ASR	L0A	Illumination regulation, in acc. with UN-R 48.06
B1F	Heating, electronic air-processing unit	L1C	LED daytime running lamps
B1H	Electr. compressed air supply and control, centre	L1W	LED turn signals in light signature
B1Z	ABS, disengageable	L2H	Side marker lamps, flashing
B2A	Disc brakes on front and rear axle	L9A	Pre-installation for rotating beacons
B2E	Disc brakes with full protection	L9G	Pre-installation for flood lamp, cab rear wall
B2X	Parking brake, electronic	M0C	Bottom shell to prevent swirling-up of dust
B4A	Condensation monitoring, for compressed air sys.	M0Q	Noise regulation acc. to UN-R 51.03, phase 2
B4L	All compressed air tanks, aluminium	M2F	Eng. OM936, inline 6, 7.7 l, 260kW (354hp), 1400 Nm
CLW	Steering oil cooling	M4X	Engine version Euro VI, E
C0J	Frame overhang 1200 mm	M5V	High Performance Engine Brake
C2N	Wheelbase 4500 mm	M6N	Air compressor, single-cylinder
C5P	Bolted frame	M7I	Insect screen in front of cooling system
C6C	Steering, single-circuit	M8A	Air intake from front
C6J	Power steering pump, uncontrolled	M9V	Deletion, guard plate, bumper
C6Q	Stabiliser, front axle	N4M	Double PTO MB 135-11b/2c, flange + MPA, med.-speed
C6Y	Stabiliser, under frame, rear axle	N6I	Transm. lock double PTO, inner PTO2 on layshaft
C7K	Battery carrier, batteries stacked	N6J	Trans. lock dbl. PTO, outer PTO1 offset to layshf.
C7Q	Free space for crane outrigger feet	N6Z	Transmission oil cooling
C8F	Wing, for chassis transit	O0A	Coolant service interval, long for non-SWR
C9S	Deletion mounting parts, on frame	O0T	TruckLive
C9Y	Deletion, rear underride guard (ECE)	O1N	Detachable parts for offline cab
D0S	Compressed-air connection, in cab	O1T	Interior colour greige/anthracite
D1C	Driver's suspension seat, comfort	O1Y	Steering, direct
D1N	Fold-up co-driver's seat	O2X	Optimised cab separation point, supply
D2Y	Seat belt monitor	O3K	Active Safety
D3Q	Seat cover, velour, driver's seat	O6U	Ctrl. code, ident.plate Europ. type approv. stage2
D3T	Seat cover, velour, co-driver's seat, centre seat	P0Q	Cover, for wheel arch and engine
D5Y	Rubber mats, driver's and co-driver's side	P0S	Space f.control unit betw. driv.seat & door pocket
D6F	Air conditioning system	Q1N	Front spring, 8.0 t, 3-leaf
D6I	Residual engine heat utilisation	Q2U	Rear spring, 13.0 t
D6Z	Construction-site filter	R0L	Tyres, customer request, FA
D7G	Stowage compartment lid, driver and co-driver side	R0N	Tyres, customer request, RA
D7Q	Stowage facility, high, on engine tunnel	R0Z	Wheel-nut cap
D8A	Roof hatch/vent, roof	R1Q	15-degree tapered rims, 9.00 x 22.5
E0D	Battery sensor, Hella	S1D	Stability Control Assist (ESP)

Orderdata (Order 1450613060)

E0F	Batteries from company Exide	S1H	Lane Keeping Assist
E0V	Highload parameter, level 1	S1L	Attention Assist
E1B	Batteries 2 x 12 V/170 Ah, low-maintenance	S1O	Traffic Sign Assist
E1N	Alternator 28 V/100 A	S1Y	Tyre pressure monitor
E2J	Automatic cutouts	S2D	Active Brake Assist 6
E3L	Socket, 24 V/15 A, co-driver footwell	S2H	Active Sideguard Assist 2
E3W	PSM, 2nd generation	S2L	Frontguard Assist
E4B	Interface, fleet management system FMS	S4A	Pre-installation for alcohol test on start-up lock
E5A	No. 1 switch, for non-MB body electrics	S5A	Speed limiter, 90 km/h (56 mph), ECE
E5B	No. 2 switch, for non-MB body electrics	S5Z	Cruise control
E5H	Switch for night-time driving light	S8A	First aid kit
E6Y	Reverse warning, comb. with hazard warning lights	S8B	Fire extinguisher, 2 kg
F0E	M-cab, low roof, 2.30 m, tunnel 320 mm	S8C	Hazard warning triangle
F0G	Side module, N3G vehicle	S8D	Warning lamp
F0Y	Mirror cover, construction vehicle	S8E	Reflective safety jacket
F1Q	M-cab	U1W	AdBlue lines, water-heated
F2C	Floor variant, tunnel 320 mm	U3D	Control code, CAN star points, classic
F2G	Cab width 2.30 m	U3F	Control code, global AdBlue sensor (GMS DEF)
F2M	Cab, 420 mm attachment height	U3S	3rd-generation electronics architecture
F2Y	ClassicSpace Low Roof	V0Q	Vehicle version in acc. w. GSR, phase B
F3A	Cab mountings, standard, steel-sprung	V0T	Vehicle class N3G, off-road vehicle
F3W	Cab tilting mechanism, mechanical-hydraulic	V0U	Overhang angle, front, minimum 25 degrees
F4I	Cab rear wall, with window	V0X	Ground clearance under front axle, minimum 250 mm
F4X	Stowage compartment exterior flap, left	V0Y	Ground clearance under rear axle, minimum 250 mm
F5L	Sun visor, exterior, transparent	V0Z	Ground clearance between axles, minimum 300 mm
F5Y	A-pillar trim	V1B	Arocs
F6D	Windscreen, tinted, with filter band	V1W	Standard
F6I	Front mirror, heated	V2J	Arocs model generation 5
F7B	Bumper, with steel corners	V5A	Specification, France
F7D	Bumper centre section w. towing eyes, coupling	V8A jaw	Chassis number FIN
F7Y	Cab entrance, left/right, movable	V9F	Technical changes model year April
F8B	2 remote control keys	W0W	Weight variant 19.0 t (8.0/13.0)
F8E	Locking system, with central locking	X1B	Instrument/labels/documentation, French
F8F	Extended central locking	X2E	Model plate, EU
F8H	2 remote control keys, additional	X2T	Maintenance Documentation
F8V	Light sensor	X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
F8W	Rain sensor	X4K	Literature in English, additional
G0R	Transmission support arms, optimised for removal	Y1B	Control of colours, high-runner colours
G0T	Predictive Powertrain Control	Y1H	Assignment of cab paintwork, NFL North
G0W	Drive program offroad	Y4J	2 wheel chocks
G2B	Transmission G 211-12/14.93-1.0	Y4Z	Compressed-air gun, with hose
G5A	Single-disc clutch	Z1H	EBS, Wabco
G5G	Mercedes PowerShift 3	Z1Z	EAPU equipment, item 3

Orderdata (Order 1450613060)

G5L	PowerShift Advanced	Z3A	Switch module 1, type A
I2G	Tyres tubeless, 315/80 R 22.5, fr./lead./trl. axle	Z3D	Switch module 2, type B
I2H	Tyres, tubeless, size 315/80 R 22.5, rear axle	Z3F	Switch module 7
I4A	Wheel arrangement 4x2	Z3H	Side marker lights, 1st pair
I5A	18.0-tonner	Z3J	Side marker lights, 3rd pair
I6B	Tipper chassis	Z3Z	Export code
I6I	Vehicle production plant Wörth	Z4O	Tank cross-section, narrow
I6K	Heavy-duty model series, new generation from	Z4Q	Tank cross-section, low 18 t
I6M	Heavy-duty vehicles from 18 t, off-road	Z5C	OM 936
I6W	Leaf suspension, rear axle	Z5G	Fan position, on crankshaft
J1M	Dig. tachograph, 2nd gen., version 2, ADR	Z5I	Fan ratio, 1:1.0
J1S	Tachograph manufacturer VDO	Z5N	PTO, double
J2I	Standard loudspeaker	Z5P	Clutch supplier F&S
J3U	Requirement: FleetBoard Manager app	Z5S	Power take-off, pump, under top edge of frame
J6C	Multimedia Cockpit, interactive	Z5T	PTO, with 4 shafts
J6W	Reversing camera, towing vehicle end	Z5X	Left-hand drive
J7A	Truck Data Center 8	Z5Y	Vehicle, for right-side traffic
J7V	Driving assistance map, Europe region	Z7J	Aluminium battery lines
J8C	Pre-fitted Card Reader for Truck Data Center	Z8E	Plausibility control code (internal)
J8U	Pre-installation for Truck Data Center 8	Z8M	CTT vehicle, conversion at Molsheim plant
J9D	Provision for fitting toll tracking	Z8P	CTT vehicle, conversion on assembly line
K0T	Main tank, left	Z8U	CTT vehicle
K1C	Tank, 290 l, left, 650 x 565 x 950 mm, aluminium	Z9A	Constructability request order, special control
K3V	AdBlue tank, 60 l, left		

SP-REQ. no.	Description
D/JZYE	ETG2 control (homologation)
W/JC7K	Battery carrier, batteries stacked
W/JC7Q	Free space for crane outrigger feet
W/JC8C	Rear wing, 2500 mm vehicle width
W/JC8G	Wing, three-piece, without EC splash guard
W/JZAP	"Putzmeister" customer vehicle
1/AHM04-40	Mercedes-Benz Molsheim
1/AJKRR	Offer: Tank moved to measure 2000 mm
1/AJZNX621A	Offer: Modification in accordance with plan number "X"
1/AJZSXP621A	Offer: Modification in accordance with spezifikation number "X"
1/A240607096	
1/JBWZ	Adaptation arrangement for air tanks
1/JLAH	2 LED work lamps at top rear of cab
1/JZNX	Modification in accordance with plan number "X"

Orderdata (Order 1450613060)

1/JZSX

Modification in accordance with
spezifikation number "X"
